



# BATTERY WATERING TECHNOLOGIES

THE LEADER IN BATTERY WATERING TECHNOLOGY™

DRAWING NUMBER: B-12-5-EU-271

12 CELL



5 PLATE

(WITH OR WITHOUT COVER)

TRAY SIZE: 23.38" X 7.40"

PUSH IN EURO STYLE CELL

REV. 0 06/22/2016



NOTE: FINAL CONNECTIONS MADE AT  
INSTALLATION

PART #	DESCRIPTION	QTY.	<b>INSTALLATION INSTRUCTIONS</b> <i>Only water batteries after charging. Do not leave unattended.</i>  1. Remove existing battery caps. 2. Ensure the electrolyte level is covering the plates in each cell. If not, add just enough water to cover the plates. 3. Following the diagram above, insert the valves into the vent holes. 4. Push straight down on each valve until it snaps into the cell. 5. Make sure all tubing remains unobstructed.
Various	Low Profile Valve	12	
08TUB6BLK	6mm Tubing	6'	<b>336-714-0448</b> <b>www.batterywatering.com</b>
09BDCAP	Dust Cap	1	
08CAP6	End Cap	2	
08T666N	T Piece 6-6-6	1	
09MBLU1	1/4" Male Connector	1	
-	-	-	
-	-	-	